

# Safety Data Sheet

according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

#### Trade name/designation

510 Absolute Black Leather Dye  
UFI: 34AW-X0DA-9004-HJJN

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Relevant identified uses

Leather tanning, dye, finishing, impregnation and care products

### 1.3 Details of the supplier of the safety data sheet

#### Supplier

Renia Gesellschaft mbH  
Ostmerheimer Straße 516 Telephone: +492216307990  
51109 Köln E-mail: info@renia.com  
Deutschland Website: www.renia.com

#### Department responsible for information

E-mail (competent person) labor@renia.com

### 1.4 Emergency telephone number

24 hr. emergency phone number: 1-800-535-5053

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Flam. Liq. 2; flammable liquids; H225 Highly flammable liquid and vapour.  
Asp. Tox. 1; Aspiration hazard; H304 May be fatal if swallowed and enters airways.  
STOT SE 3 Narcotic effects; STOT-single exposure; H336 May cause drowsiness or dizziness.  
Skin Irrit. 2; Skin corrosion/irritation; H315 Causes skin irritation.

### 2.2 Label elements

#### Hazard pictograms



GHS02 GHS07 GHS08

#### Signal word

Danger

#### \* Hazard statements

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
H315 Causes skin irritation.

#### \* Precautionary statements

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P103 Read carefully and follow all instructions.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P261 Avoid breathing vapours.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves and eye/face protection.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

# Safety Data Sheet

according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

P312	Call a POISON CENTER if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use extinguishing powder or sand to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial incineration plant.

## Hazard components for labelling

- \* acetone; propan-2-one; propanone
- \* hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

## 2.3 Hazards not otherwise classified (HNOC)

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## SECTION 3: Composition/information on ingredients.

### 3.2 Mixtures

#### Description

leather dye based on azo- and azine-colours, dissolved in a mixture of organic solvents.

#### Hazardous ingredients

CAS No.	Substance name	weight-%
* 67-64-1	<b>acetone; propan-2-one; propanone</b> Flam. Liq. 2 H225 / Eye Irrit. 2 H319 / STOT SE 3 H336	35,0 < 50,0
* -	<b>hydrocarbons, C6-C7, isoalkanes, cyclics, &lt;5% n-hexane</b> Flam. Liq. 2 H225 / Asp. Tox. 1 H304 / Skin Irrit. 2 H315 / STOT SE 3 H336 / Aquatic Chronic 2 H411	20,0 < 25,0
* 64-17-5	<b>ethanol; ethyl alcohol</b> Flam. Liq. 2 H225 / Eye Irrit. 2 H319	20,0 < 25,0
* 1330-20-7	<b>xylene</b> Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Acute Tox. 4 H312 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Acute Tox. 4 H332 / STOT SE 3 H335 / STOT RE 2 H373	1,0 < 5,0

#### Remark

Full text of H-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General information

- \* In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### Following inhalation

- \* Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

- \* Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

- \* Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

- \* If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### Self-protection of the first aider

First aider: Pay attention to self-protection!

### 4.2 Most important symptoms and effects, both acute and delayed

#### Symptoms

- \* In all cases of doubt, or when symptoms persist, seek medical advice.

# Safety Data Sheet

according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

## 4.3 Indication of any immediate medical attention and special treatment needed

- \* First Aid, decontamination, treatment of symptoms.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

- \* alcohol resistant foam, Carbon dioxide (CO<sub>2</sub>), Powder, spray mist, (water)

#### Unsuitable extinguishing media

- \* Strong water jet

### 5.2 Special hazards arising from the substance or mixture

- \* Inhaling hazardous decomposing products can cause serious health damage. Flammable. Vapours can form explosive mixtures with air.

### 5.3 Advice for firefighters

- \* Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- \* Ventilate affected area. Do not breathe vapours.

### 6.2 Environmental precautions

- \* Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3 Methods and material for containment and cleaning up

#### For containment

- \* Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

#### For cleaning up

- \* Clean using cleansing agents. Do not use solvents.

### 6.4 Reference to other sections

- \* Safe handling: see section 7  
Personal protection equipment: refer to section 8  
Disposal: see section 13

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advices on safe handling

- \* Avoid contact with skin, eyes and clothes. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe). Personal protection equipment: see section 8 Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### Advices on general occupational hygiene

- \* When using do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

- \* Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### Hints on joint storage

- \* Keep away from strongly acidic and alkaline materials as well as oxidizers.

**Storage class** LGK3 - Flammable liquids

#### Further information on storage conditions

- \* Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Store in a well-ventilated and dry room at temperatures between 10 °C and 30 °C.

### 7.3 Specific end use(s)

# Safety Data Sheet

according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

\* Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
* 67-64-1	acetone; propan-2-one; propanone	ACGIH	- / - (-) mg/m <sup>3</sup>
* 67-64-1	acetone; propan-2-one; propanone	IDLH	- / - (-) mg/m <sup>3</sup>
* 67-64-1	acetone; propan-2-one; propanone	NIOSH	590 / - (-) mg/m <sup>3</sup>
* 67-64-1	acetone; propan-2-one; propanone	OSHA	2,400 / - (-) mg/m <sup>3</sup>
* 64-17-5	ethanol; ethyl alcohol	ACGIH	- / - (-) mg/m <sup>3</sup>
* 64-17-5	ethanol; ethyl alcohol	IDLH	- / - (-) mg/m <sup>3</sup>
* 64-17-5	ethanol; ethyl alcohol	NIOSH	1,900 / - (-) mg/m <sup>3</sup>
* 64-17-5	ethanol; ethyl alcohol	OSHA	1,900 / - (-) mg/m <sup>3</sup>
* 1330-20-7	xylene	ACGIH	- / - (-) mg/m <sup>3</sup>
* 1330-20-7	xylene	IDLH	- / - (-) mg/m <sup>3</sup>
* 1330-20-7	xylene	NIOSH	435 / 655 (-) mg/m <sup>3</sup>
* 1330-20-7	xylene	OSHA	435 / - (-) mg/m <sup>3</sup>

#### Additional information

Long-term: Long-term occupational exposure limit value  
short-term: short-term occupational exposure limit value

#### Biological limit values

CAS No.	Substance name	Source	Value/ Test material
* 67-64-1	acetone; propan-2-one; propanone	ACGIH-BEI	25 mg/L / urine end of exposure or end of shift
* 1330-20-7	xylene	ACGIH-BEI	1.5 g/g creatinine / urine end of exposure or end of shift

#### DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
* 67-64-1	acetone; propan-2-one; propanone	DNEL acute inhalative (systemic)	2,420 mg/L
* 67-64-1	acetone; propan-2-one; propanone	DNEL long-term inhalative (systemic)	1,210 mg/L
* 67-64-1	acetone; propan-2-one; propanone	DNEL long-term dermal (systemic)	186 mg/kg
* 64-17-5	ethanol; ethyl alcohol	DNEL long-term dermal (systemic)	343 mg/kg bw/day
* 64-17-5	ethanol; ethyl alcohol	DNEL long-term inhalative (systemic)	950 mg/m <sup>3</sup>
* 64-17-5	ethanol; ethyl alcohol	DNEL acute inhalative (local)	1,900 mg/m <sup>3</sup>
* -	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term dermal (systemic)	773 mg/kg
* -	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term inhalative (systemic)	2,035 mg/m <sup>3</sup>
* 1330-20-7	xylene	DNEL long-term inhalative (systemic)	77 mg/m <sup>3</sup>
* 1330-20-7	xylene	DNEL acute inhalative (systemic)	289 mg/m <sup>3</sup>
* 1330-20-7	xylene	DNEL acute inhalative (local)	289 mg/m <sup>3</sup>
* 1330-20-7	xylene	DNEL long-term dermal (systemic)	180 mg/kg bw/day

#### DNEL Consumer

CAS No.	Substance name	DNEL type	DNEL value
---------	----------------	-----------	------------

# Safety Data Sheet

according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

*	67-64-1	acetone; propan-2-one; propanone	DNEL long-term dermal (systemic)	62 mg/kg
*	67-64-1	acetone; propan-2-one; propanone	DNEL long-term inhalative (systemic)	200 mg/L
*	67-64-1	acetone; propan-2-one; propanone	DNEL long-term oral (repeated)	62 mg/kg
*	64-17-5	ethanol; ethyl alcohol	DNEL long-term oral (repeated)	87 mg/kg bw/day
*	64-17-5	ethanol; ethyl alcohol	DNEL long-term dermal (systemic)	206 mg/kg bw/day
*	64-17-5	ethanol; ethyl alcohol	DNEL long-term inhalative (systemic)	114 mg/m <sup>3</sup>
*	64-17-5	ethanol; ethyl alcohol	DNEL acute inhalative (local)	950 mg/m <sup>3</sup>
*	-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term dermal (systemic)	699 mg/kg
*	-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term inhalative (systemic)	608 mg/m <sup>3</sup>
*	-	hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	DNEL long-term oral (repeated)	699 mg/kg
*	1330-20-7	xylene	DNEL long-term inhalative (systemic)	14.8 mg/m <sup>3</sup>
*	1330-20-7	xylene	DNEL long-term dermal (systemic)	108 mg/kg bw/day
*	1330-20-7	xylene	DNEL long-term oral (repeated)	1.6 mg/kg bw/day

## PNEC

CAS No.	Substance name	PNEC type	PNEC Value	
*	67-64-1	acetone; propan-2-one; propanone	PNEC aquatic, freshwater	10.6 mg/L
*	67-64-1	acetone; propan-2-one; propanone	PNEC aquatic, marine water	1.06 mg/L
*	67-64-1	acetone; propan-2-one; propanone	PNEC sediment, freshwater	30.4 mg/L
*	67-64-1	acetone; propan-2-one; propanone	PNEC sediment, marine water	3.04 mg/L
*	67-64-1	acetone; propan-2-one; propanone	PNEC soil, marine water	29.5 mg/L
*	64-17-5	ethanol; ethyl alcohol	PNEC aquatic, freshwater	0.96 mg/L
*	64-17-5	ethanol; ethyl alcohol	PNEC aquatic, marine water	0.79 mg/L
*	64-17-5	ethanol; ethyl alcohol	PNEC sediment, freshwater	3.6 mg/kg
*	64-17-5	ethanol; ethyl alcohol	PNEC sediment, marine water	2.9 mg/kg
*	1330-20-7	xylene	PNEC aquatic, freshwater	0.327 mg/L
*	1330-20-7	xylene	PNEC aquatic, marine water	0.327 mg/L
*	1330-20-7	xylene	PNEC sewage treatment plant (STP)	6.58 mg/L
*	1330-20-7	xylene	PNEC sediment, freshwater	12.46 mg/kg
*	1330-20-7	xylene	PNEC sediment, marine water	12.46 mg/kg
*	1330-20-7	xylene	PNEC soil, freshwater	2.31 mg/kg

## 8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

### Personal protection equipment

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Hand protection

Suitable material: NBR (Nitrile rubber)

Thickness of the glove material  $\geq$  0.4 mm

Breakthrough time  $\geq$  480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin.

Recommended glove articles: EN ISO 374

# Safety Data Sheet

## according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

### Skin protection

- \* Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

### Eye/face protection

- \* Eye glasses with side protection

### Body protection

- \* When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

### Environmental exposure controls

- \* Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	Liquid
Colour	black
Odour	characteristic
pH at 20 °C	not determined
Melting point/freezing point	< -35 °C
Initial boiling point and boiling range	40 - 110 °C
Flash point	-18 °C
flammability	not applicable
Lower explosion limit at 20°C	1 Vol-%
Upper explosion limit at 20°C	15 Vol-%
Vapour pressure at 20°C	240 mbar
Relative vapour density	not applicable
Density at 20 °C	0.785 kg/L
Water solubility at 20°C	not determined
Partition coefficient: n-octanol/water	see section 12
Ignition temperature in °C	200 °C
Decomposition temperature	not determined
Dynamic viscosity at 20 °C	3.5

### 9.2 Other information

not applicable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

- \* No specific test data related to reactivity available for this product or its ingredients.

### 10.2 Chemical stability

- \* Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

### 10.3 Possibility of hazardous reactions

- \* Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

### 10.4 Conditions to avoid

- \* Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

### 10.5 Incompatible materials

- \* No further relevant information available.

### 10.6 Hazardous decomposition products

- \* Hazardous decomposition byproducts may form with exposure to high temperatures e.g.: Carbon dioxide (CO<sub>2</sub>), Carbon monoxide, smoke.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

# Safety Data Sheet

according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

## **Acute toxicity**

Based on available data, the classification criteria are not met.

### \* **acetone; propan-2-one; propanone**

LD50: oral (Rat): = 5,800 mg/kg

\* LD50: dermal (Rabbit): > 15,800 mg/kg

LC50: inhalative (Rat): = 76 ppmV (4 h)

### \* **ethanol; ethyl alcohol**

LD50: (Rat): = 10,470 mg/kg; (OECD 401)

\* LD50: (Rabbit): > 2,000 mg/kg; (OECD 402)

\* LC50: (Rat): 117 < x > 125 mg/L (4 h); (OECD 403)

### \* **hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**

LD50: (Rat): > 5,000 mg/kg; (OECD 401)

\* LC50: (Rat): > 20 mg/L (4 h); (OECD 403)

\* LD50: dermal (Rabbit): > 2,000 mg/kg; (OECD 402)

### \* **xylene**

LD50: oral (Rat): = 3,523 mg/kg

\* LD50: dermal (Rabbit): = 12,126 mg/kg

\* LC50: inhalative (Rat): = 27,571 mg/m<sup>3</sup> (4 h)

## **Skin corrosion/irritation**

Causes skin irritation.

## **Serious eye damage/eye irritation**

\* Based on available data, the classification criteria are not met.

## **Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

### \* **Overall assessment on CMR properties**

Based on available data, the classification criteria are not met.

## **STOT-single exposure**

May cause drowsiness or dizziness.

## **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

May be fatal if swallowed and enters airways.

## **Practical experience/human evidence**

\* Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## **11.2 Information on other hazards**

### \* **Endocrine disrupting properties**

\* This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

\* Based on available data, the classification criteria are not met.

#### ***Acute (short-term) fish toxicity***

### \* **acetone; propan-2-one; propanone**

LC50: (Oncorhynchus mykiss (Rainbow trout)): = 5,540 mg/L (96 h)

### **ethanol; ethyl alcohol**

\* LC50: (Oncorhynchus mykiss (Rainbow trout)): = 13,000 mg/L (96 h)  
Method: OECD 203

# Safety Data Sheet

according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

- \* **hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**  
LC50: (Oncorhynchus mykiss (Rainbow trout)): = 11.4 mg/L (96 h)
- \* **xylene**  
LC50: (Oncorhynchus mykiss (Rainbow trout)): = 2.6 mg/L (96 h)
- \* **Acute (short-term) toxicity to algae and cyanobacteria**
- \* **acetone; propan-2-one; propanone**  
ErC50: = 100 mg/L (96 h)
- \* **ethanol; ethyl alcohol**  
EC50 (Scenedesmus capricornutum): = 12,900 mg/L (48 h)  
Method: OECD 201
- \* **ethanol; ethyl alcohol**  
EC50 (Scenedesmus capricornutum): = 275 mg/L (72 h)  
Method: OECD 201
- \* **hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**  
EL50: (Pseudokirchneriella subcapitata): = 30 < x > 100 mg/L (72 h)
- \* **xylene**  
ErC50: = 2.2 mg/L (72 h)
- \* **Acute (short-term) toxicity to crustacea**
- \* **acetone; propan-2-one; propanone**  
EC50 (Daphnia pulex (water flea)): = 8,800 mg/L (48 h)
- \* **ethanol; ethyl alcohol**  
EC50 (Daphnia magna (Big water flea)): = 12,340 mg/L (48 h)
- \* **hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**  
EL50: (Daphnia magna (Big water flea)): = 3 mg/L (48 h)
- \* **xylene**  
EC50 (Daphnia magna (Big water flea)): = 1 mg/L (48 h)

## 12.2 Persistence and degradability

- \* **ethanol; ethyl alcohol**  
Biodegradation; (Activated sludge) = 70 % (5 d)  
Method: OECD TG 301D  
Readily biodegradable (according to OECD criteria).
- \* **hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane**  
Biodegradation; (Activated sludge) = 81 % (28 d)  
Method: OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D  
Readily biodegradable (according to OECD criteria).

## 12.3 Bioaccumulative potential

- \* **ethanol; ethyl alcohol**  
Partition coefficient: n-octanol/water  
Method: calculated
- \* Partition coefficient: n-octanol/water = -0.24
- \* Partition coefficient: n-octanol/water = -0.32

## 12.4 Mobility in soil

No information available.

## 12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6\* Endocrine disrupting properties

No information available.

## 12.7 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### \* Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way.

# Safety Data Sheet

according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

## Waste codes/waste designations according to EWC/AVV

080111\* - Waste paint and varnish containing organic solvents or other dangerous substances

## Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

## SECTION 14: Transport information

### 14.1 UN number or ID number

UN 1263

### 14.2 UN proper shipping name

#### \* Land transport (US DoT 49 CFR)

Paint

#### Sea transport (IMDG)

Paint

#### Air transport (ICAO-TI / IATA-DGR)

Paint

### 14.3 Transport hazard class(es)

* Land transport (US DoT 49 CFR)	3
Sea transport (IMDG)	3
Air transport (ICAO-TI / IATA-DGR)	3

### 14.4 Packing group

* Land transport (US DoT 49 CFR)	II
Sea transport (IMDG)	II
Air transport (ICAO-TI / IATA-DGR)	II

### 14.5 Environmental hazards

* Land transport (US DoT 49 CFR)	not applicable
Sea transport (IMDG)	not applicable

### 14.6 Special precautions for user

- \* Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.  
Advices on safe handling: see parts 6 - 8

### 14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

### 14.8 Additional information

#### \* Land transport (US DoT 49 CFR)

Tunnel restriction code: D/E

- \* Limited quantity (LQ): 5 Liter  
Hazard identification number (Kemler No.): 33

#### Sea transport (IMDG)

- \* EmS-No.: F-E, S-E  
Limited quantity (LQ): 5 Liter

#### Air transport (ICAO-TI / IATA-DGR)

not applicable

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### National regulations

- \* Observe in addition any national regulations!
- \* SARA Title III Section 311/312 Hazard Categories: Refer to section 2 of the safety data sheet.

## SECTION 16: Other information

### List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.

# Safety Data Sheet

## according to US OSHA Hazard Communication Standard (29 CFR 1910.1200)

510  
Version 4.3

Absolute Black Leather Dye  
Revision date Dec 7, 2023

Print date Jan 19, 2024

H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
H411	Toxic to aquatic life with long lasting effects.

### Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

:

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic

PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

### Indication of changes

\* Data changed compared with the previous version.